



AFRL-RX-WP-TP-2008-4048

FULL-FIELD VIBRATION MEASUREMENT FOR VIBROTHERMOGRAPHY (PREPRINT)

Jeremy Renshaw and Stephen D. Holland
Iowa State University

NOVEMBER 2007

Approved for public release; distribution unlimited.

See additional restrictions described on inside pages

STINFO COPY

**AIR FORCE RESEARCH LABORATORY
MATERIALS AND MANUFACTURING DIRECTORATE
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7750
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YY) November 2007		2. REPORT TYPE Conference Paper Preprint		3. DATES COVERED (From - To) 24 November 2006 – 24 November 2007	
4. TITLE AND SUBTITLE FULL-FIELD VIBRATION MEASUREMENT FOR VIBROTHERMOGRAPHY (PREPRINT)				5a. CONTRACT NUMBER FA8650-04-C-5228	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 63112F	
6. AUTHOR(S) Jeremy Renshaw and Stephen D. Holland				5d. PROJECT NUMBER 3153	
				5e. TASK NUMBER 40	
				5f. WORK UNIT NUMBER 41300100	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Iowa State University Ames, IA 50011				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory Materials and Manufacturing Directorate Wright-Patterson Air Force Base, OH 45433-7750 Air Force Materiel Command United States Air Force				10. SPONSORING/MONITORING AGENCY ACRONYM(S) AFRL/RXLP	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RX-WP-TP-2008-4048	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES Conference paper submitted to the Proceedings of the 2007 Review of Progress in Quantitative NDE Conference. This work was funded in whole or in part by Department of the Air Force contract FA8650-04-C-5228. The U.S. Government has for itself and others acting on its behalf an unlimited, paid-up, nonexclusive, irrevocable worldwide license to use, modify, reproduce, release, perform, display, or disclose the work by or on behalf of the U. S. Government. PAO Case Number: WPAFB 07-0151, 19 Oct 2007. Paper contains color.					
14. ABSTRACT Vibrothermography is a nondestructive technique for finding defects through vibration-induced heating imaged with an infrared camera. To model the crack heating process in vibrothermography, it is essential first to understand the vibration that causes heat generation. We describe a method for calculating internal motions from surface vibrometry measurements. A reciprocity integral and Gauss's law allow representation of internal motion by a surface integral of boundary motion times the Green's Function. We present experimental results showing internal motions calculated from measured surface motions of a vibrating sample. This will ultimately allow estimation of the detectability of a hypothetical crack at an arbitrary location in a specimen.					
15. SUBJECT TERMS Vibrothermography, Sonic IR, Dynamic Stress, Vibration Measurement					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 12	19a. NAME OF RESPONSIBLE PERSON (Monitor) Thomas J. Moran 19b. TELEPHONE NUMBER (Include Area Code) N/A
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			

FULL-FIELD VIBRATION MEASUREMENT FOR VIBROTHERMOGRAPHY

Jeremy Renshaw¹ and Stephen D. Holland²

¹Center for NDE and Mat Sci & Eng Dept, Iowa State Univ, Ames, Iowa 50011

²Center for NDE and Aerospace Eng Dept, Iowa State Univ, Ames, Iowa 50011

ABSTRACT. Vibrothermography is a nondestructive technique for finding defects through vibration-induced heating imaged with an infrared camera. To model the crack heating process in Vibrothermography, it is essential first to understand the vibration that causes heat generation. We describe a method for calculating internal motions from surface vibrometry measurements. A reciprocity integral and Gauss's law allow representation of internal motion by a surface integral of boundary motion times the Green's Function. We present experimental results showing internal motions calculated from measured surface motions of a vibrating sample. This will ultimately allow estimation of the detectability of a hypothetical crack at an arbitrary location in a specimen.

Keywords: Vibrothermography, Sonic IR, Dynamic Stress, Vibration Measurement

PACS: 43.40.-r, 07.10.Lw, 87.63.Hg, 62.30.+d

INTRODUCTION

We demonstrate a method that measures internal stresses and strains of a vibrating part [1] through surface velocimetry. This allows for a direct calculation of the internal stresses and strains at any point within an object. The mathematics involved in this process are similar to those of the Boundary Element Method (BEM). Understanding the internal vibration around a crack may lead to a relation between the stresses and strains around the crack and the observed heating in Vibrothermography. The ultimate goal of this research is to understand the physics of the crack heating process.

THEORY

The equation of motion governing a solid body is given as [2]

$$\tau_{ij,i} + f_j = \rho \ddot{u}_j \quad (1)$$

with stress tensor τ_{ij} , a body force f_j , density ρ , and displacement u_j . Following the notation used in Achenbach [3], the time-harmonic Green's Function with stress $\tau_{ij:k}^{G:X}$ and displacement $u_{j:k}^{G:X}$ [4] is the solution to Equation 1 given a time harmonic impulse body force in the k 'th direction.

$$\tau_{ij:k,i}^{G:X} + \delta(\underline{x} - \underline{X})e^{-i\omega t}\delta_{jk} = \rho\ddot{u}_{j:k}^{G:X}, \quad (2)$$

The body force is applied at $x = X$ and it is expressed as $f_j = \delta(\underline{x} - \underline{X})e^{-i\omega t}\delta_{jk}$. The reciprocity formulation of Equation 1 is given as Equation 2 multiplied by u_j minus Equation 1 multiplied by $u_{j:k}^{G:X}$.

$$\tau_{ij:k,i}^{G:X}u_j - \tau_{ij,i}u_{j:k}^{G:X} = (\rho\ddot{u}_{j:k}^{G:X} - \delta(\underline{x} - \underline{X})e^{-i\omega t}\delta_{jk})u_j - \rho\ddot{u}_ju_{j:k}^{G:X}. \quad (3)$$

Equation 3 can be simplified due to symmetry and integrated over the specimen volume. Several of the terms in the equation can be grouped and represented as a divergence. Then, these terms can be transformed through the divergence theorem into a surface integral. The remaining terms are the volume integral of a spatial Dirac delta

$$\int_V (\delta(\underline{x} - \underline{X})e^{-i\omega t}\delta_{jk}u_j)dV = - \int_S (\tau_{ij:k}^{G:X}u_j - \tau_{ij}u_{j:k}^{G:X})n_idA, \quad (4)$$

where n_i is the normal to the part surface at a given location. The surface tractions for this experimental setup are assumed to be zero; therefore, $\tau_{ij}u_{j:k}^{G:X} = 0$ and the equation can be written as

$$\int_V (\delta(\underline{x} - \underline{X})e^{-i\omega t}\delta_{jk}u_j)dV = - \int_S (\tau_{ij:k}^{G:X}u_j)n_idA, \quad (5)$$

Solving the volume integral thus allows us to calculate the displacement at any given point X as

$$u_k|_{\underline{x}=\underline{X}} = \frac{1}{e^{-i\omega t}} \int_S (-\tau_{ij:k}^{G:X}u_j)n_idS. \quad (6)$$

Equation 6 shows us that the internal displacement at a point is calculated from a surface integral of the boundary displacement times the Green's Function stress. As the laser vibrometer measures velocity, not displacement, the displacement can be obtained simply through a time integral of the measured velocity. Once the internal displacements are known, the strain can be calculated from the spatial derivative of the displacements. Stress can then be calculated through the use of Hooke's Law. Therefore, the strain and displacement at any point within a part can be calculated from a knowledge of the vector surface velocity of the part. Stress can then be calculated given the material properties of the part in question. A major benefit of this method is that the Green's Function drops off as $1/R$ in the far field, so the effect of areas that cannot be measured is limited to the immediate vicinity of the missed points.

EXPERIMENTAL PROCEDURE

The vector surface velocity of the specimen is needed to calculate its internal stresses and strains. The vector surface velocity is determined by measuring surface velocity with a laser vibrometer from three linearly independent incident directions. The laser vibrometer measures one-dimensional vibration using the doppler shift in the direction of the beam reflected back from the specimen surface; thus three measurements are needed to obtain the complete vibration of a point. Two in-plane measurements are obtained by rotating the sample by means of a motion control system. A third, out-of-plane measurement is obtained using the motion control system and a carefully-aligned mirror to redirect the beam. The




FIGURE 1. Stress as a function of time at a point in the bar using spatial differentiation and Hooke's Law.

motion control system is programmed to scan the measurement beam across the entire surface of the part. As some points - namely those near the transducer - are shadowed and not possible to measure, a few points will always be missed.

A titanium bar 6 inches long, 1 inch wide, and 1/2 inch thick was fastened to a piezoelectric transducer. We covered the bar in retroreflective tape to maximize the reflected optical signal returning to the laser vibrometer. To minimize shadowed areas, the attachment to the transducer was the bar's only means of support. We positioned the bar on a carefully-aligned motion control system and vibrated it using a 100-20000 Hz frequency sweep at low amplitude ensuring repeatable vibration and stresses well within the linear elastic regime. The bar was tessellated into 5mm by 5mm areas and scanned from three selected linearly independent incident directions. The measured data were numerically integrated using Equation 6 to calculate the internal motion of the sample.

RESULTS

The full stress tensor τ_{ij} for any point within the bar can be determined using the derivative of Equation 6 and Hooke's Law. For any frequency, an Inverse Fourier transform gives the stress as a function of time instead of frequency for a given point within the bar. For example, the cross-sectional shearing stress τ_{yz} at a selected point within the test bar is shown in Figure 1. Any component of the stress tensor at any location inside the bar can be accurately calculated and expressed quantitatively, with the exception of the shaded areas near the transducer.

The test bar exhibited several resonances at frequencies within the sweep. One such resonance, a flexural resonance occurring at 7.40kHz, will be examined in more detail. The




FIGURE 2. 7.4 kHz resonant mode shape measured with the laser vibrometer. Stress τ_{xx} of this mode has been mapped to color.




FIGURE 3. Mode profile of the 7.4 kHz resonant mode and the best-fit flexural mode shape. The curve fit is: $y = -.272 \sinh(\kappa x) + .272 \cosh(\kappa x) + .337 \sin(\kappa x) - .226 \cos(\kappa x) \mu\text{m}/\text{kHz}$. The two curves are superimposed nearly on top of one another.




FIGURE 4. Color mapped images of the measured and calculated stresses.

mode shape of this resonance is shown in Figure 2 with the values of stress mapped to color. The region of the bar that appears flat was the area that was shadowed by the transducer. All other parts of the bar appear to follow a flexural wave mode shape and can be fit to the flexural wave solution. Flexural wave theory allows four parameters to fit the displacement profile of a mode. The allowed parameters are coefficients of $\sin(kx)$, $\cos(kx)$, $\sinh(kx)$, and $\cosh(kx)$ where k is the wave number and x is the longitudinal position along the bar. These four parameters were fit to the observed shape of the 7.40kHz mode. The velocity profile and the four parameter fit to flexural wave theory are shown in Figure 3.

The four parameters obtained from the best fit to flexural wave theory can be used to evaluate the stress profile in the bar. The τ_{xx} stress is given for the cross-sectional slice of the bar and mapped to color in Figure 4. These values match to within 5% for all areas not shaded by the transducer or its immediate vicinity, corresponding to $x < 35$ mm on the lower left-hand side of the upper bar in Figure 4.

One major advantage of this method for determining stress is shown in Figure 5. This figure shows two missed data points, one on the upper part of the specimen and another near the lower edge. Though these points have a zero velocity, their effects on the surrounding areas quickly drop off as $1/R$.

CONCLUSIONS

We have demonstrated a method to calculate the dynamic stress tensor at all points within a vibrating object through the use of surface vibrometry. These results were found to compare to within 5 percent - except in the immediate vicinity of shaded regions - of those calculated based on flexural wave theory using the four parameters shown in Figure 3. The use of the Green's Function and the reciprocity integral formulation allow the measurement to be done even when one or more faces of an object are not measurable, since the influence of missed points or areas dies away with a $1/R$ dependence from such locations. This method shows promise to accurately correlate internal stresses and strains at a crack face to the observed heating in Vibrothermography.




FIGURE 5. Effect of missed data points on surrounding areas. The bar is color mapped to velocity

ACKNOWLEDGEMENTS

This material is based upon work supported by the Air Force Research Laboratory under Contract #FA8650-04-C-5228 at Iowa State University's Center for NDE

REFERENCES

1. C.P. Burger *Handbook on Experimental Mechanics*, edited by A. S. Kobayashi, 260-276, 1987.
2. S. Kobayashi, "Elastodynamics," *Computational Methods in Mechanics Vol. 3 Boundary Element Methods in Mechanics*, edited by D. E. Beskos, 1987.
3. J. D. Achenbach, *Reciprocity in Elastodynamics*, 90-94, 2003.
4. N. Kame and T. Yamashita, "Simulation of the spontaneous growth of a dynamic crack without constraints on the crack tip path," *Geophysical Journal International* **139**(2), 345-358, Nov. 1999.